

DENSITY METERS

FAST, RELIABLE MEASUREMENTS USING THE OSCILLATING U-TUBE METHOD

MADE IN
GERMANY







CUTTING-EDGE TECHNOLOGY, MADE IN GERMANY

A.KRÜSS Optronic is a leading manufacturer of high-precision measuring devices and analytical instruments. The family enterprise founded in 1796 offers an extensive range of products and customised solutions for quality assurance in the pharmaceutical, chemical, petrochemical, food and beverage industry as well as for research and science. Whether it is a refractometer, polarimeter, density meter, gas analyser, flame photometer, melting point meter or microscope – our instruments meet the highest requirements in terms of speed, accuracy and reliability. Thanks to our strong R&D capacities, we are a driving force in the technology market setting the standards for functional scope and user-friendliness. A dense network of sales partners and certified service partners allows us to provide individual consultation as well as optimised service and support for our customers around the globe.

OVER 200 YEARS OF PIONEERING SPIRIT AND SUCCESS



SUCCESS FACTOR DENSITY MEASUREMENT	4
OUR DENSITY METER SETS	6
A STRONG PERFORMANCE PACKAGE	8
MAXIMUM EFFICIENCY THROUGH AUTOMATION	10
OUR EXTENSIVE RANGE OF SERVICES	12
FEATURES AND TECHNICAL DATA OF OUR DENSITY METERS	13
OVERVIEW OF DENSITY METER SETS AND CONSUMABLES	14




SUCCESS FACTOR DENSITY MEASUREMENT

A comprehensive quality assurance covering the entire production process is a must in any industrial sector. Density measurements are frequently used for this purpose, especially in the pharmaceutical, chemical, petrochemical as well as the food and beverage industry. They allow the manufacturer to analyse raw materials, semi-finished and finished products as well as the manufacturing steps in terms of a number of factors.

Density can be used to identify substances, to determine their quality or purity and to measure their concentration in binary or quasi-binary mixtures. Substance conversions and reaction dynamics can also be inferred from it. In combination with other methods such as refractometry that measures the refractive index of substances, the density measurement allows you to make precise state

ments about the quality of each step of the production process. This requires that the measured samples are kept at an exact temperature as the density depends strongly on the temperature. A change by 0.1 °C would mean a deviation of the measurement value between 0.0001 and 0.0003 g/cm³.

However, reliable measurement results are not enough in today's general economic conditions. The ever increasing cost and efficiency pressure calls for density measurement solutions that can be easily integrated into any production process, manage with very little sample volumes and deliver fast results. Of the three density measurement methods used nowadays – the areometric, pycnometric and oscillating U-tube method –, the latter method best meets these requirements.



DENSITY MEASUREMENT METHODS

AREOMETER

The areometer works on the principle of buoyancy as a function of mass. The glass float sinks into the liquid sample until its mass-dependent weight force and the buoyancy force are in equilibrium. The density that corresponds to the depth of immersion is shown on the scale inside the float column. An areometer is inexpensive but difficult to read in case of highly viscous or dark samples and very fragile. It also requires a sample volume of at least 100 ml and the maximum measurement accuracy of 0.001 g/cm³ demands a lengthy exact temperature control.

PYCNOMETER

The pycnometer – a glass flask whose inner volume can be very precisely determined and reproduced – is a device used for measuring the gravimetric density. You first weigh the empty flask and then the one filled with the liquid sample. The density is then calculated from the measured weight of the sample. A pycnometer can be used for a wide temperature and pressure range and is more accurate than an areometer. However, the measurement takes several hours due to the elaborate weighing and requires skilled personnel.

U-TUBE OSCILLATOR

This method takes advantage of the fact that the oscillation frequency of a body is a function of its mass. A U-shaped capillary is filled with the liquid sample and piezoelectric or magnetic oscillations are induced. The mass and thus the density of the sample can be calculated from the resulting eigenfrequency of the U-tube oscillator. Density meters using the oscillating U-tube method allow for a highly accurate measurement at a controlled temperature and with easily reproducible results within minutes, require a sample volume of no more than 1 ml and are easy to handle.



FOCUS ON QUALITY

WITH DENSITY METERS
FROM A.KRÜSS

OUR DENSITY METER SETS

In close cooperation with industry and science, we have developed digital density meters with U-tube oscillators that best meet the requirements in terms of accuracy, speed, required sample volume and ease of integration into the manufacturing process. They have stood the test for many years in numerous companies for quality control in the laboratory as well as at the production line.

Our DS7000 density meters are available in two versions – DS7700 and DS7800. Their only difference lies in the measuring accuracy; all other characteristics are identical. The devices are very robust, compact and yet precise and suitable for nearly all liquids, emulsions, pastes etc. thanks to the chemical-resistant parts made of borosilicate glass and PTFE that are in contact with the sample.

The samples are supplied manually via syringe, semi-automatically via peristaltic pump or fully automatically via auto-sampler. Highly viscous samples are usually supplied with a syringe; low-viscous to slightly viscous samples can also be supplied with a peristaltic pump or an autosampler. We provide suitable density meter sets for any working method and any type of sample that include all the required accessories from tube sets to nozzles and adaptors to splash guards for the manual supply of aggressive substances.

Once the measurement has started, the measuring chamber and the sample will be maintained at the right temperature and the display will quickly show the measured values on the selected scales. Whether it is the density, the relative density, Brix, the concentration of alcohol or sulphuric acid or other user-configured scales – the possibilities are almost unlimited.

The user can also choose between two measurement methods: the measurement with a manual measurement time input and an optimised measurement time thanks to automatic stability recognition. Our devices will always require a sample volume of less than 1 ml. The U-tube oscillator is cleaned by rinsing it with the appropriate medium supplied with a syringe or peristaltic pump. Just one keystroke is needed to have the drying unit eliminate all liquid residues. The drying unit DS7060 with its 3/2-way valve allows for a fully automatic drying.

Our density meters feature a self-explanatory, well-arranged user interface, which makes it easy even for non-expert personnel to operate the device. A state-of-the-art TFT display ensures a clear, bright representation of all the information. The integrated touch-screen tops off the convenient user experience.

YOUR ADVANTAGES

- Suitable sets for all applications
- Intuitive operation via touch-screen display
- Optional user administration with two authorisations
- Easy, menu-guided adjustment
- Freely assignable shortcut keys
- Any number of freely configurable methods
- Predefined scales (density, relative density, Brix, concentration of alcohol and sulphuric acid)
- Any number of freely definable scales with conversions based on tables or formulas
- Requires only a small sample volume
- Measurements of highly viscous or very problematic samples
- Sample supply via syringe, peristaltic pump or autosampler
- Efficient Peltier temperature control
- Manual measurement time input or optimised measurement time thanks to automatic stability recognition
- Multiple measurements with averaging
- Compact, robust cast aluminium housing
- Chemical-resistant materials
- Interfaces for the convenient transfer of measured values
- Extensive connections for peripheral equipment
- Compliance with GMP/GLP, 21 CFR Part 11 etc.
- IQ/OQ/PQ by A.KRÜSS Optronic or one of our certified service partners
- Service, maintenance, calibration and adjustment on site

Manual sample supply with **DS7800**
via syringe



MANUAL SAMPLE SUPPLY

SET M

SET SA

SET A

SAMPLE SUPPLY	Manual via Syringe	Semi-automatic via Peristaltic pump; Manual via Syringe	Fully automatic via Peristaltic pump Autosampler; Manual via Syringe
RECOMMENDED FOR	Low sample volume	Moderate to high sample volume	High sample volume
	Any degree of viscosity (Low-viscous to highly viscous)	Low-viscous to slightly viscous samples	
	Common & aggressive samples	Common & aggressive samples, whereby contact with users is reduced	
ADVANTAGES	Samples with a high viscosity can be measured	Semi-automatic sample supply, cleaning and drying	Fully automatic sample supply, cleaning and drying
	Tube sets suitable for any type of sample		
DENSITY METER	DS7700 with a measurement accuracy of ± 0.001 g/cm ³ or DS7800 with a measurement accuracy of ± 0.0001 g/cm ³		
DRYING UNIT	DS7060 with 3/2-way valve		
PERISTALTIC PUMP	Can be retrofitted	DS7070	
AUTOSAMPLER	Can be retrofitted (requires drying unit DS7060)	Can be retrofitted (requires drying unit DS7060)	AS80 or AS90, each with 1 of 2 types of sample plates and suitable polypropylene or glass vials
TUBE SETS FOR SAMPLE SUPPLY AND DISCHARGE	DS7073-M2 Tube set for manual filling	DS7073-SA Tube set for semi-automatic filling	DS7073-A Tube set for fully automatic filling
ORDER NUMBERS*	DS7700-M/DS7800-M	DS7700-SA/DS7800-SA	DS7700-A/DS7800-A

*For a detailed overview of our density meter sets, please refer to page 14 f

A STRONG PERFORMANCE PACKAGE

UNLIMITED NUMBER OF METHODS



- Create any number of methods and analyse each sample using the desired parameters
- Measurement modes: single, continuous or interval measurement
- Method parameters such as scales, temperature, sample supply, limit values, comments and many others
- Pre-defined scales such as density, relative density, Brix, concentration of alcohol and sulphuric acid
- Any number of freely definable scales with conversions based on tables or formulas such as m%, vol%, g/cm³ und many more

COMPLETE DATA RECORDING AND BACKUP



- Records all measured data as well as system or method selections in a tamper-proof measured data storage
- Documentation of all measured values of the last 999 measurements with consecutive numbering
- Audit trail for logging configuration changes
- Data reports with own logo

INTUITIVE OPERATION



- State-of-the-art touch-screen display
- Uniform operation of all A.KRÜSS laboratory devices
- Displays measured value in two measurement units
- Freely assignable speed buttons for the most important functions
- Easy to understand, menu-guided adjustment
- A choice of six languages (de, en, es, fr, it, pt)

FLEXIBLE DATA EXPORT



- Printout on serial ASCII printer (real paper)
- Printout on network printer in PDF or PS format
- Printout as PDF on USB flash drive or to network share
- Export in HTML or CSV format on USB flash drive or to network share
- Can be connected to a keyboard, mouse, barcode scanner
- Easy integration into existing networks (DHCP-Client) or a LIMS



DENSITY METER SOLUTIONS FOR ANY NEED

- DS7700 with an measurement accuracy of $\pm 0.001 \text{ g/cm}^3$
- DS7800 with an measurement accuracy of $\pm 0.0001 \text{ g/cm}^3$
- Set M for manual sample supply
- Set SA for semi-automatic sample supply
- Set A for fully automatic sample supply



COMPLIANCE WITH GLOBAL STANDARDS AND NORMS

- GMP/GLP
- 21 CFR Part 11
- Pharmacopoeia (USP, BP, JP, Ph. Eur.)
- FDA, ISO, HACCP, OIML, ASTM, ICUMSA, NIST



FAST, RELIABLE MEASUREMENT

- Drying unit with regenerable silica gel for a high-precision adjustment
- Efficient Peltier temperature control
- Measurement with manual measurement time input or optimised measurement time thanks to automatic stability recognition
- Preview of measured values updated every second



EASY FILLING AND CLEANING

- Manual, semi-automatic or fully automatic sample supply
- Including drop collector, splash guard optional
- Reliable filling check via inspection glass
- Chemical-resistant materials such as borosilicate glass and PTFE
- Freely configurable cleaning processes
- Semi-automatic or fully automatic drying (optional)



INTELLIGENT USER ADMINISTRATION

- Can be activated or deactivated as required
- Different authorisation levels
- Setup of user profiles
- Customized settings for different users or work groups



MAXIMUM EFFICIENCY THROUGH AUTOMATION

TYPES OF SAMPLE SUPPLY

MANUAL

If work is performed manually, the sample and the medium for cleaning the U-tube oscillator will be supplied with a Luer syringe. While the sample is added, you can check for air bubbles by looking through the inspection glass. A suitable medium is injected for the cleaning until all sample residues have been dissolved and removed. The drying unit will then remove all liquid residues.

SEMI-AUTOMATIC

The semi-automatic process requires the peristaltic pump DS7070, which will draw the required volume of the sample or the cleaning medium into the U-tube oscillator. Depending on which integrated drying unit is used, there is no need to interchange the drain tube and air tube when you switch from the sample supply or cleaning to the drying process.

FULLY AUTOMATIC

Together with the peristaltic pump DS7070, the AS80 and AS90 autosamplers allow for a fully automatic process. The samples on the autosampler's rotating plate are removed successively by the suction needle and drawn into the U-tube oscillator by the peristaltic pump. If desired, the system can be automatically rinsed and dried after each measurement.



SEMI-AUTOMATIC



Semi-automatic sample supply
with **DS7800** via peristaltic pump **DS7070**

SEMI-AUTOMATIC SOLUTIONS

In case of low-viscous to slightly viscous samples, it is possible to perform a semi-automatic sample supply and cleaning of the U-tube oscillator using the peristaltic pump DS7070. This means higher efficiency and more safety if aggressive or harmful substances are analysed. It also improves the reproducibility of the measurement results and saves costs as syringes do not need to be resupplied. The drying unit DS7060 allows for a fully automatic drying: It is directly connected to the peristaltic pump, and via its 3/2-way valve, the flow of the sample or cleaning medium and the drying air is regulated. The DS7060 also has a high resistance to chemicals as the parts that come into contact with the sample are made of FFKM and PVDF.

Peristaltic pump DS7070

- Inexpensive, durable peristaltic pump, especially for use with A.KRÜSS laboratory instruments
- For low-viscous to slightly viscous samples; the revolution speed can be precisely set on the density meter
- Pump tube made of TPE and highly resistant against many common samples, also aggressive samples such as dilute hydrochloric or sulphuric acid (at room temperature)
- Low-pulsation sample transfer thanks to 8-roller head
- Direct connection to drying unit DS7060 with 3/2-way valve so that a fully automatic drying is possible without having to interchange tubes
- With autosampler AS80 or AS90, it can be used for a fully automatic sample supply
- High-quality and robust metal housing
- Easy change of tubes within seconds

ADVANCED TECHNOLOGY FOR DENSITY METER 2024

New touch screen technology with 7.0 inch display

- Operation is via capacitive touchscreens with fast computing unit
- The glass surface can be operated with gloves and cleaned with solvents
- The 18-bit colour depth delivers 262,000 colours and produces clear images
- Glare effects in sunlight are reduced to a minimum

Higher data security with better authorisation concepts

- From now on with specific setting of network access restrictions
- Enhanced authentication methods with Secure Login
- The combination of user name & password protects saved data from unauthorised access
- Audit trail to record configuration changes
- Possibility of data reports with own logo

Fully automatic sample supply
with **DS7800** via Autosampler **AS90**



FULLY AUTOMATIC

FULLY AUTOMATIC SOLUTIONS

In working environments with a high sample throughput, fully automatic executions of the entire process - from the sample supply to the cleaning and drying - are useful if they are flexible, powerful and robust.

Our AS80 and AS90 autosamplers are the suitable products to meet these high requirements. Together with the peristaltic pump DS7070, they allow for an unsupervised measurement of up to 89 samples.

You can set any number of individual measurement methods, cleaning processes and sampler templates on the user interface of the density meters. The AS80 and AS90 models require very little space, are easy and fast to install and very durable. They come with a sample plate and a set of polypropylene or glass vials.

Autosampler AS80 and AS90

- Also suitable for aggressive and low-viscous samples
- Two options are available for each autosampler:
AS80-T18: 18 x 50 ml (42 mm x 43 mm) or
AS80-T36: 36 x 30 ml (28 mm x 65 mm);
AS90-T53: 53 x 16 ml (22 mm x 55 mm) or
AS90-T89: 89 x 6 ml (16 mm x 55 mm)
- Sets of polypropylene vials or glass vials are available
- Sample supply via peristaltic pump DS7070
- Integrated rinse port
- Optional model with a penetrable membrane
- Suitable for measuring stations with more than one analysis device (requires LIMS software)
- Control via the serial interface (RS-232) of the density meters

OUR EXTENSIVE RANGE OF SERVICES



YOUR BENEFITS AS AN A.KRÜSS CUSTOMER

- IQ/OQ/PQ by A.KRÜSS Optronic or certified service partners
- Service, maintenance, calibration and adjustment on site
- Calibration and adjustment with certified calibration liquids
- Training and application consulting on site
- Spare parts and accessories directly from the manufacturer
- Customer-specific customisation of devices
- Efficient support thanks to a fast confirmability of the customer's situation based on extensive reports

CALIBRATION AND ADJUSTMENT

We recommend to have our density meters DS7700 and DS7800 calibrated and adjusted once a year exclusively by A.KRÜSS Optronic or by one of our certified service partners. Our calibration protocols and certificates are GMP-/GLP-compliant and thus one component that ensures a GMP-/GLP-compliant work. For the calibration and adjustment of our density meters, we use certified, PTB-traceable calibration liquids (PTB = Physikalisch-Technische Bundesanstalt, The National Metrology Institute of Germany). A calibration and an adjustment are usually completed within a very short period of time so that any interference with the operational processes of our customers is minimised.

MAINTENANCE OF OUR DENSITY METERS

Our maintenance contracts include the following services:

- Response time of no more than 48 hrs and phone support during office hours, e. g. technical support in case of faults
- Maintenance of the devices named in the maintenance contract including functional check and safety inspection, cleaning of all components important for the proper function as well as calibration with certified calibration liquids and, if necessary, adjustment
- Provision of the required certified calibration liquids as well as measuring, control and special tools
- Firmware updates if they are required for the functionality of the devices
- Should repairs be required within the scope of maintenance work, we will charge for the required spare parts separately. We will grant a one year guarantee on replacement and spare parts
- Provision of rental equipment to bridge the time required for maintenance, calibrations, adjustments and repairs. Maintenance customers will have preferential rights on rental equipment
- Preparation of GMP-/GLP-compliant maintenance and calibration protocols
- Guarantee extension from 12 to 36 months as a part of agreed maintenance services.

FEATURES AND TECHNICAL DATA OF OUR DENSITY METERS

FEATURES

- Measurement based on U-tube oscillation
- Easy operation thanks to self-explanatory, well-arranged user interface and touch-screen display
- User administration that can be activated or deactivated depending on the requirements, with optional password protection and different user rights
- Easy, menu-driven adjustment
- Any number of measurement methods for monitoring the measurement process according to method, batch, product and/or production line incl. limit value monitoring
- Measurement modes: single, continuous or interval measurement
- Measurement procedures: measurement with manual measurement time input or optimised measurement time thanks to automatic stability recognition
- Requires only a small sample volume
- Samples are supplied via syringe, peristaltic pump or autosampler
- Efficient Peltier temperature control
- Short measurement period
- Compact, robust cast aluminium housing
- Chemical-resistant materials (borosilicate glass and PTFE)
- Luer or UNF connections
- Drying unit included
- Integrated air pressure sensor
- Tamper-proof data storage (saves the last 999 measurements)
- Customised layout of the result reports
- Interfaces for the convenient transfer of measured values (USB, Ethernet, RS-232)
- Compliance with GMP/GLP, 21 CFR Part 11, pharmacopoeias (USP, BP, JP, Ph. Eur.), FDA, ISO, HACCP, OIML, ASTM, ICUMSA, NIST

TECHNICAL DATA

SCALES	Density [g/cm ³], Relative Density, Brix [%Brix], Concentration of alcohol [vol%], Concentration of sulphuric acid [wt%] User-defined
MEASUREMENT RANGE	0–3 g/cm ³
MEASUREMENT ACCURACY	DS7700: ±0.001 g/cm ³ ; DS7800: ±0.0001 g/cm ³
MEASUREMENT PERIOD	Typically 1–3 minutes including temperature control
SAMPLE VOLUME IN CASE OF MANUAL INJECTION	0.9 ml
AMBIENT TEMPERATURE	10–40 °C
TEMPERATURE CONTROL RANGE	10–40 °C
TEMP. MEASUREMENT ACCURACY	±0.02 °C
METHODS	A practically unlimited number of methods can be set
MANUFACTURER'S CALIBRATION	With air and water at 9 temperatures each
ADJUSTMENT	Automatic (menu-driven), with dried air and distilled water
CONTROL	7.0" - capacitive touch-screen, 800 x 480 Pixel
HOUSING	Aluminium cast, powder-coated
INTERFACES	1x USB, 1x RS-232, 1x Ethernet
OPERATING VOLTAGE	100–240 V, 47–63 Hz
POWER CONSUMPTION (OPERATION)	25 W
POWER CONSUMPTION (MAX.)	120 W
DIMENSIONS (W X H X D)	220 mm x 220 mm x 430 mm
WEIGHT	5.3 kg

OVERVIEW OF DENSITY METER SETS AND CONSUMABLES

ORDER NUMBER	SETS AND SET COMPONENTS
DS7700-M / DS7800-M	SET M FOR MANUAL SAMPLE SUPPLY, CONSISTING OF:
DS7700 oder DS7800	Density meter with glass U-tube oscillator, measurement accuracy $\pm 0.001 \text{ g/cm}^3$ or $\pm 0.0001 \text{ g/cm}^3$
DS7060	Drying unit with 3/2-way valve
DS7007	1x (each) filling nozzle Luer & UNF (already installed)
DS7009	Luer syringe, 2 ml, 10 pieces
DS7010	Luer syringe, 10 ml, 10 pieces
DS7019	PE waste container with lid, 600 ml
DS7073-M2	PTFE-tube (350 mm; UNF to UNF), PTFE waste tube (350 mm; UNF); with suitable hose connections

DS7700-SA / DS7800-SA	SET SA FOR SEMI-AUTOMATIC SAMPLE SUPPLY, CONSISTING OF:
DS7700 oder DS7800	Density meter with glass U-tube oscillator, measurement accuracy $\pm 0.001 \text{ g/cm}^3$ or $\pm 0.0001 \text{ g/cm}^3$
DS7060	Drying unit with 3/2-way valve
DS7070	Peristaltic pump
DS7007	1x (each) filling nozzle Luer & UNF (already installed)
DS7009	Luer syringe, 2 ml, 10 pieces
DS7010	Luer syringe, 10 ml, 10 pieces
DS7019	PE waste container with lid, 600 ml
DS7073-SA	PTFE hose set (suction hose 450 mm; drain hose 400 mm; connection hose 400 mm; waste hose 450 mm; spare hose 450 mm); with suitable UNF hose connections
DS7022	Adapter UNFi/Luer for sample supply through PTFE tube via Luer filling nozzle
DS7071	Tube set for peristaltic pump DS7070, consisting of: TPE pump tube (105 mm), 5 pieces; PTFE tube connection UNF, 2 pieces

DS7700-A / DS7800-A	SET A FOR FULLY AUTOMATIC SAMPLE SUPPLY, CONSISTING OF:
DS7700 oder DS7800	Density meter with glass U-tube oscillator, measurement accuracy $\pm 0.001 \text{ g/cm}^3$ or $\pm 0.0001 \text{ g/cm}^3$
DS7060	Drying unit with 3/2-way valve
DS7070	Peristaltic pump
AS80 oder AS90	Autosampler for 18 or 36 samples, including: sample plate 18x 50 ml (42 mm x 43 mm) or 36x 30 ml (28 mm x 65 mm) set polypropylene vials (50 ml) or glass vials (30 ml); other vials on request PTFE connecting tube or Autosampler for 53 or 89 samples, including: sample plate 53x 16 ml (22 mm x 55 mm) or 89x 6 ml (16 mm x 55 mm) set polypropylene vials (16 or 6 ml); other vials on request PTFE connecting tube
DS7007	1x (each) filling nozzle Luer & UNF (already installed)
DS7009	Luer syringe, 2 ml, 10 pieces
DS7010	Luer syringe, 10 ml, 10 pieces
DS7019	PE waste container with lid, 600 ml
DS7073-A	PTFE hose set (suction hose 450 mm; drain hose 400 mm; connection hose 400 mm; waste hose 450 mm; spare hose 450 mm); with suitable UNF hose connections
DS7022	Adapter UNFi/Luer for sample supply through PTFE tube via Luer filling nozzle
DS7071	Tube set for peristaltic pump DS7070, consisting of: TPE pump tube (105 mm), 5 pieces; PTFE tube connection UNF, 2 pieces

ORDER NUMBER	CALIBRATION LIQUIDS
DS7011	DAkKS-certified density standard high-purity water, 0.9982 g/cm ³ at 20 °C (second point at 15 °C), 10 ml
DS7012	DAkKS-certified density standard isooctane, 0.6900 g/cm ³ at 20 °C (second point at 15 °C), 10 ml
DS7013	DAkKS-certified density standard n-nonane, 0.7200 g/cm ³ at 20 °C (second point at 15 °C), 10 ml
DS7014	DAkKS-certified density standard dichlorotoluene, 1.2500 g/cm ³ at 20 °C (second point at 15 °C), 10 ml
DS7015	DAkKS-certified density standard tetrachloroethene, 1.6200 g/cm ³ at 20 °C (second point at 15 °C), 10 ml

MATERIAL OF OUR PRODUCTS IN CONTACT WITH SAMPLES

We offer suitable solutions for any type of sample. Refer to the table to see of which materials the parts in contact with the samples are made of. We will gladly assist you in the selection of the products.

COMPONENT	PART	MATERIAL
Density meters DS7700, DS7800	Measuring cell	Borosilicate glass
	Luer/UNF nozzles	PTFE
Drying unit DS7060	3/2-way valve	FFKM, PVDF
Autosampler AS80, AS90	Vials	PP/glass
	Connecting tube	PTFE
Tube sets DS7030-M, DS7030-SA, DS7030-A	All parts in contact with the sample	PTFE
Luer syringes DS7009, DS7010	–	PE/PP
Waste container DS7019	–	PE
Adaptors DS7022	–	PTFE
Tube sets DS7071	Pump tube	TPE
	Tube connections UNF	PTFE



A.KRÜSS Optronic GmbH
Alsterdorfer Straße 276–278
22297 Hamburg | Germany

Tel. +49 40 514317-0
Fax +49 40 514317-60

E-Mail info@kruess.com
Web www.kruess.com

